



## FDLED-4-B9W-3-4-5K-WH

### 4" Slim Baffle 3 CCT Switchable 9W

#### Features

##### Body

Durable airtight aluminum body with etched white polycarbonate diffuser lens for low glare.

##### LED Characteristics

This general application light fixture features a 9 watt LED module that maintains uniform intensity producing up to 500 lumens ;with a typical CRI of 80 and a 50,000 hour life span .Available in 3000K or 4000K color temperature

##### Dimming

100%-10% dimming capability .This fixture is compatible with industry standard TRIAC/ELV dimmers (contact factory for listing of compatible dimmers).

##### Beam Spread

The fixture lens provides 120° beam spread.

##### Mounting

Includes two spring loaded clips to attached to any ceiling material .The slim profile allows to be mounted under joists or duct work.

##### LED Driver

Extruded aluminum hardwire box with 210mA dimmable class II electronic LED driver with 100-135V AC input. Includes an 7" cable from driver to fixture.

##### Operating Temperature

-20°C~40°C

##### Environment

Suitable for wet locations.  
Suitable for insulated ceiling applications.


#### SPECIFICATION

Application	Ceiling Recess Mount
Approved Location	Wet
Beam Angle	120°
CCT	3000°K / 4000°K / 5000°K
Certifi cation	cETLus
Class II	Yes
Colour	WH
CRI	80
Dimming	Yes
Dimming Tech	TRIAC/ELV
Input	100-135V AC, 60Hz, 0.11A
LM79	Yes
LM80	Yes
Lumens	550 / 600 / 660
Lumens per Watt	58.3
Power Factor	>0.9
Projected Life	70% @ 50,000 hrs
Warranty	10 Years
Wattage	9W



#### Description

The panel is a 9 watt 4" slim profile light fixture for recess retrofit application. It is a high-preformance, easy to install residential grade downlight solution that offers good light output energy efficiency and streamlined design. Suitable for damp locations. For use in soffits.



Notes : Accessories are sold separately. For additional options please consult your representative . Due to our continued efforts to improve our products , products specifications are subject to change without notice.

#### Accessories



**FD-FLEX-10**  
10FT Flexible connector, for use with Slim LED fixtures.



**FD-MP-4**  
4-1/4" Round pre-mounting plate for Slim LED round fixtures.



**FD-FLEX-20**  
20FT Flexible connector, for use with Slim LED fixtures.