


Low-p rofile, edge-lit design

Features


- Edge-lit technology, no glare or dark spots, instant-on
- No existing recessed housing or junction box required
- Dimming TRIAC 10% to 100%
- I.C. rated for direct contact with insulation
- Suitable for DAMP LOCATION
- Rated for a long life - over 50,000 hours
- Pre-Select 5 CCT - 2700K, 3000K, 3500K, 4000K, 5000K



DIMENSIONS



INSTALLATION




Accessories (Optional)


Extension Cables



Mounting Plate



4 Inch Trim



SPECIFICATIONS	
Model	FDLED-4-R12W-5CCT-SQ
Watts	12W
Light Ouput(lm)	700lm
Size	4-inch
Default Driver Input	AC120V,60HZ
Color Temperature(K)	Pre-Select 5CCT - 2700K, 3000K, 3500K, 4000K, 5000K
CRI	80Ra
Dimming	Triac Dimming
Power Factor	>0.9
Approved Location	DAMP Location
Air Tight	Yes
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	120°
PACKAGE	
Weight.(g)	405g
Qty/CTN (pcs)	18pcs/CTN
Box Dimension	465*275*250 mm
Gross Weight	8kg/CTN