


Regressed Module Downlight





Trim Finish Options

• WHITE BLACK

Decription

3" Regressed Module Downlight

Features

- * Interchangeable Trims
- * Available shapes: Round and Square
- * Type IC, Air-Tight & Suitable for Wet Location No Housing Required
- * Fast Installation & No Junction Box Needed
- * Includes two spring loaded clips to attach to any ceiling material.
- * 10%-100% dimming capability. This fixture is compatible with industry standard forward-phase / reverse-phase and TRIAC/ELV dimmers
- * Rated for long life over 50,000 hours





















DIMENSIONS








Module 3" Round Trim

3" Square Trim

SPECIFICATIONS Model FDRS-3-10W-5CCT-120V-R Watts 10W 80Ra+ Pre-Select 5CCT Color Temperature(K) 2700K/3000K/3500K/4000K/5000K Light Ouput(Im) 650lm Default Driver Input AC120V, 60Hz Triac Dimming 10-100% Dimming Power Factor >0.9 Approved Location Wet Location Air Tight Yes IC Rated Yes (-4°F~104°F) -20~40°C Operating Temp. Beam Angle 90°

PACKAGE	
Weight.(g)	440g
Qty/CTN (pcs)	18pcs/CTN
Box Dimension	L345xW300xH305mm
Gross Weight	9.42kg/CTN

INSTALLATION



INCLUDED IN BOX

• 3" Regressed Module Downlight and Remote Driver





OPTIONAL ACCESSORIES

Interchangeable Trims Square / White Square / Black


Factory Direct Lighting (2020) Ltd. www.fdlighting.ca Tel: 1-855-533-0743 / 1-905-944-1210

Mounting Plate



FD-UNMP (SKU#101078)

Universal Mounting Plate, compatible with 2", 3", 3.5", 4" Light Panel and Downlights



Pre-Mouting Plate for 3" Gimbal and Slim LED Light Panel (78mm hole size)

Flexible Connector



10ft/20ft flexible connector

Emergency Power Pack



SKU#110502 AC120-347 VAC 50/60Hz, emergency time 90 mins

100 Shields Court Unit B Markham, Ontario Canada, L3R 9T5