We Sell Directly to Contractors

Pre-Select 5 CCT 4" Trimless LED Downlight

FDTL-LED-4-15W-5CCT-BK **SKU#101075**



Trim Finish Options

• BLACK • WHITE





Features

- * Durable airtight aluminum body
- * Type IC, Air-Tight & Wet No Housing Required
- * Flangeless installation, provide a more high end looking
- * No housing required, easy and fast installation
- * 10%-100% dimming capability. This fixture is compatible with industry standard forward-phase / reverse-phase and TRIAC/ELV dimmers
- * Rated for long life over 50,000 hours

Color Temperature(K)	Pre-Select 5 CCT 2700K/3000K/3500K/4000K/5000K
Light Ouput(Im)	1000lm
Default Driver Input	AC120V, 60Hz
Dimming	Triac Dimming 10% - 100%
Power Factor	>0.99
Approved Location	Wet Location
Air Tight	Yes
Operating Temp.	(-4°F~104°F) -20~40°C
Beam Angle	38°

SPECIFICATIONS

FDTL-LED-4-15W-5CCT-WH / FDTL-LED-4-15W-5CCT-BK

15W

80Ra+

PACKAGE	
Weight.(g)	672g
Qty/CTN (pcs)	18 pcs/CTN
Box Dimension	495(L) x 365 (W) x 310(H) mm
Gross Weight	15.12 kg/CTN

Intertek


















DIMENSIONS



INCLUDED IN BOX

Model


Watts

CRI


- 4" Trimless LED Downlight-15 watts, with Driver
- 4 Screws



INSTALLATION







ACCESSORIES (Optional)

Mounting Plates



3-3/4" new construction pre-mounting plate opening Ø3-3/4"(95mm)



2"/3"/3.5"/4" new construction pre-mounting plate opening Ø2-1/8"(54mm), Ø2-7/8"(72mm), Ø3-3/4"(95mm), Ø5-1/4"(132mm)

Flexible Connector

