

LED Circular Up and Down Light

PRODUCT DESCRIPTION

FDL LED round flat panel design for high-end interiors, offices, hotels, retail, and other commercial/home projects. It incorporates advanced light guide plate technology and high brightness micro-SMD LED light source to deliver a smooth, up&down and uniform light fixture. This unique round flat panel luminaire designed to provide smooth, dispersed illumination for modern interior spaces. Featuring a low-profile aluminum construction, the Circa is convenient and durable for installation in ceilings with a low plenum space. The Circa incorporates innovative Flat Optics that are engineered to eliminate glare issues that have become increasingly prevalent among LED luminaires as efficacy has increased over time.

FEATURES:

- Surge protector.
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel.
- Low profile design optimizes shipping, storage, and handing.
- Shallow depth provides sleek, low-profile appearance.
- Performance engineered opticallens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance.
- Driver disconnect provided where required to comply with US and Canadian codes.
- Class II/P driver, with 0-10V or Triac dimming.

APPLICATIONS:

Home/Offices/Hotels Restaurants & café Shops/Meeting rooms

ORDERING:

(KK=CCT, can be 30, 35, 40, 50) (The lumens are tested with frosted









| OPTIONS: | Order Code |
|-----------------------------|-------------|
| AC347-480V High Voltage | 347V |
| CCT 3000K,3500K,4000K,5000K | 30/35/40/50 |
| Suspension Chain | SC |

















| Item | Watts | Efficacy | Lumens | CRI | PF | Voltage | Dimension(L*W*H):Inch | |
|--------------|-------|------------------|---------|-----|-------|-------------------|-----------------------|---|
| FDCS-30-120M | 30W | 100lm/w | 3,000lm | >80 | >0.95 | 120 - 277V | Ø 15" | 1 |
| FDCS-40-120M | 40W | 100lm/w | 4,000lm | >80 | >0.95 | 120 - 277V | Ø 19" | 1 |
| FDCS-50-120M | 50W | 100 l m/w | 5,000lm | >80 | >0.95 | 120 - 277V | Ø 23" | 1 |



LED Circular Up and Down Light

Illustration

